Please rewrite claims 1, 7 and 13 as follows:

- 1. (Twice amended) A method for controlling a device for recording or reproducing an optical recording medium having control information recorded in a wobbled form on a signal track, the method comprising the steps of:
- (a) detecting a wobbled signal from a signal track for reading the control information, wherein said detecting step is carried out in a free running state in which only a focus servo is turned on; and
- (b) performing tracking control using a tracking servo after the detection of the wobbled signal.
- 7. (Twice amended) A method for controlling a device for recording or reproducing an optical recording medium having control information recorded in a wobbled form on a signal track, the method comprising the steps of:
- (a) detecting a wobbled signal from a signal track for detecting the present rotating speed of the optical recording medium, wherein said detecting step is carried out in a free running state in which only a focus servo is turned on;
- (b) fixing a target rotating speed of the optical recording medium with reference to the detected present rotating speed of

Serial No 09/741,170 Docket No. 465-791P Art Unit 2653 Page 3

the optical recording medium, and controlling the optical recording medium to the target rotating speed; and

(c) turning on a tracking servo for a regular recording or reproduction after the target rotating speed of the optical recording medium has been fixed with reference to the wobbled signal.

13. (Twice amended) A device for controlling a device for recording or reproducing an optical recording medium having control information recorded in a wobbled form on a signal track, the device comprising:

a tracking servo for performing tracking control on the optical recording medium;

a wobble detecting part for detecting a wobbled signal formed by wobbling from the signal track at a time when only a focus servo is turned on and the tracking servo is not operating;

an information reading part for reading control information from the detected wobbled signal; and

a servo controlling part for using the control information in a regular recording or reproduction.

D